CONTINUOUSLY VARIABLE TRANSMISSION FLUID

Recommended for Toyota CVT fluid FE standard. Realizes smooth and comfortable ride with high power transmission performance!

TCL CVTF FE is specially designed for belt type CVT cars. Suppresses slipping of CVT belt and pulley with optimum friction performance, and provides comfortable acceleration with reliable torque transmission. Keeps excellent thermal oxidation stability even in CVT with constantly high temperature, and with high shear stability, maintains the performance of fluid for a long time, to reliably protect CVT.



CCVTF FE FULLY SYNTHETIC CVTF FE FULLY SYNTHETIC FULLY SYNTHETIC FULLY SYNTHETIC CVTF FE FULLY SYNTHETIC FULLY SYNTHET FULLY SYNTHET FULLY SYNTHET FULLY SYNTHET FULLY SYNTHET FULLY SYNTHET FULLY SYNTHET

Item Code	Package
A001TYFE	1L×20pcs
A004TYFE	4L×6pcs
A020TYFE	20L×1pc

Tanikawa Chemical Laboratory

FLUD FLUD F

CONTINUOUSLY VARIABLE TRANSMISSION FLUID

CVTF

FULLY SYNTHETIC

CVTF FE



- Compatible with TOYOTA CVTF FE and can be used for cars which are recommended to use CVTF FE.
- Meeting the technical requirements of the latest type CVT which is becoming higher performance, provides comfortable drive-feeling and reliability.
- With excellent power-transmission performance, firmly transmits the power from the engine to CVT belt, and provides smooth, reliable shifting and comfortable driving.
- Excellent low temperature fluidity improves transmission efficiency and startability, and improves lubrication even in low temperature conditions.
- Cannot be used for cars with NISSAN Extroid CVT.
- Do not use for AT cars.
- Before exchanging CVTF, make sure to check CVT has no problem or damage. Note that replacing CVTF without adequate confirmation may cause any trouble.

Representative physical properties

Appearance		Clear Brown	
Density (15°C)	g/cm³	0.8522	
Color (ASTM)		L1.5	
Flash point (COC)	°C	208	
Pour point	°C	-55.0	
Viscosity (-40°C)	mPa∙s	12,800	
Kinematic viscosity (40°C)	mm*/s	35.81	
Kinematic viscosity (100°C)	mm*/s	7.239	
Viscosity index		172	
Base number (PCA)	mgKOH/g	2.26	
Foaming test (Seq II)	ml	20/0	

Specifications

Usage	Continuously Variable Transmission Fluid		
Product Line	CVTF		
Product Name	TCL CVTF FE		
Base Oil	Fully Synthetic		



CVTE

OF

全合成油へ 品質CVT用

TF FE

URL:www.tanikawayuka.co.jp

