

**HIGH PERFORMANCE
ENGINE OIL**

EURO LINE C3/SP 5W-30

**ACEA standard designation,
suitable for luxury European cars
considering fuel-efficient.**

Acquired ACEA C3 standard and is recommended for European designated imported vehicles. It is ideal for European gasoline and diesel vehicles equipped with GPF and DPF. In addition to acquiring ACEA C3 standard, also acquires API standard SP Resource Conserving and ILSAC GF-6A standards, and it compatible to excellent oil evaporation, engine protection performance, fuel saving performance, compatibility with exhaust gas aftertreatment devices, and the long life performance required for the latest engine oils.

EURO LINE

FULLY SYNTHETIC

C3/SP 5W-30



Item Code	Package
E0010530C3	1L × 20pcs
E0040530C3	4L × 6pcs
E0200530C3	20L × 1pc
E2000530C3	200L × 1drum

Tanikawa Chemical Laboratory

TCL®

EURO LINE C3/SP 5W-30

HIGH PERFORMANCE
ENGINE OIL



EURO LINE
FULLY SYNTHETIC
C3/SP 5W-30

■ Product features

- Mixing fully synthetic base oil and high performance additives provide stable oil film properties from low to high RPM ranges, with emphasis on engine durability, and protecting the engine from high temperatures and oxidation.
- Suppresses engine sludge, keeps the inside of the engine clean, and prevents the decline in engine performance.
- Suitable for eco-friendly gasoline vehicles and European standard clean diesel vehicles.
- In gasoline vehicles, it maintains the performance of the catalytic converter for a long period of time, and in clean diesel vehicles, it prevents the diesel particulate filter from clogging up.

■ Representative physical properties

Density (15°C)	g/cm ³	0.8529
Color (ASTM)		L3.0
Flash point (COC)	°C	228
Pour point	°C	-47.5
Viscosity (-30°C)	mPa·s	5,290
Kinematic viscosity (40°C)	mm ² /s	64.45
Kinematic viscosity (100°C)	mm ² /s	12.00
Viscosity index		186
Base number (PCA)	mgKOH/g	8.08
Foaming test (Seq II)	ml	0/0

■ Specifications

Usage	Gasoline · Diesel engine oil for European cars
Product Line	EURO LINE
Product Name	TCL ENGINE OIL EURO LINE ACEA C3 / SP 5W-30
Standard	ACEA C3 / API SP GF-6A
Base Oil	Fully Synthetic
Viscosity	5W-30



TCL

TANIKAWA YUKA KOGYO CO.,LTD.
1-13-11, Yako, Tsurumi-ku, Yokohama, 230-0001, Japan

URL: www.tanikawayuka.co.jp

