

**HIGH PERFORMANCE  
ENGINE OIL**

# EURO LINE C3/SP 5W-40

## ACEA standard designation, suitable for luxury European cars equipped with GPF/DPF!

Acquired ACEA C3 standard and is recommended for European designated imported cars. It is suitable for European gasoline and diesel vehicles equipped with GPF and DPF. In addition to acquiring ACEA C3 standard, it also has API SP standard, and has excellent oil evaporation, engine protection performance, compatibility with exhaust gas aftertreatment devices, and long life performance required for the latest engine oils.

## EURO LINE

FULLY SYNTHETIC

**C3/SP 5W-40**



Item Code	Package
E0010540C3	1L×20pcs
E0040540C3	4L×6pcs
E0200540C3	20L×1pc
E2000540C3	200L×1drum

Tanikawa Chemical Laboratory

**TCL**®



# EURO LINE C3/SP 5W-40

HIGH PERFORMANCE  
ENGINE OIL



**EURO LINE**  
FULLY SYNTHETIC  
**C3/SP 5W-40**

## Product features

- Mixing fully synthetic base oil and high performance additives provide stable oil film properties from low to high RPM ranges, with emphasis on engine durability, and protecting the engine from high temperatures and oxidation.
- Suppresses engine sludge, keeps the inside of the engine clean, and prevents the decline in engine performance.
- Suitable for eco-friendly gasoline vehicles and European standard clean diesel vehicles.
- In gasoline vehicles, it maintains the performance of the catalytic converter for a long period of time, and in clean diesel vehicles, it prevents the diesel particulate filter from clogging up.

## Representative physical properties

Density (15°C)	g/cm <sup>3</sup>	0.8529
Color (ASTM)		L3.0
Flash point (COC)	°C	228
Pour point	°C	-47.5
Viscosity (-30°C)	mPa·s	5,290
Kinematic viscosity (40°C)	mm <sup>2</sup> /s	64.45
Kinematic viscosity (100°C)	mm <sup>2</sup> /s	12.00
Viscosity index		186
Base number (PCA)	mgKOH/g	8.08
Foaming test (Seq II)	ml	0/0

## Characteristics list

Usage	Gasoline・Diesel engine oil for European cars
Product Line	EURO LINE
Product Name	TCL ENGINE OIL EURO LINE ACEA C3 / SP 5W-40
Standard	ACEA C3 / API SP
Base Oil	Fully Synthetic
Viscosity	5W-40



**TCL**

TANIKAWA YUKA KOGYO CO.,LTD.  
1-13-11, Yako, Tsurumi-ku, Yokohama, 230-0001, Japan

URL: [www.tanikawayuka.co.jp](http://www.tanikawayuka.co.jp)

